

PolyCompact / SPM 1000 *dig*

Modular SAT-TV-head end for community systems



Type	SPM 1000 <i>dig</i>
Article no.	5525110
module plug-in slots	10
LNB-supply	18 VDC 250 mA per input / max. 0,4 A
Frequency range	47- 862 MHz
Return loss	≥ 14 dB
Output level 10 channels	100 dBμV
Power supply	180 - 265 V~ 50/60 Hz
Power consumption	max. 95 W
Housing (W x H x D)	433 x 244 x 177 mm
operating temperature	0 - 50°C

Base unit SPM 1000 *dig*

- Modular headend for small and medium sized systems
- Easy programming by LCD-Display
- 10 module slots
- ideal for residence complex, hotels and hospitals
- LNB supply at every input
- Easy combination of several units
- Wall mounting or installation into 19" cabinet

Base units SPM 100 and SPM 200

- For the insert of one (SPM100) or two (SPM200) modules of the PolyCompact serie
- Integrated programming unit and amplifier
- Example SPM 200: one slot for a digital twin module and one slot for a twin modulator

SPM 100

for all analogue single modules except the SPM-TT

SPM 100 - T

for the twin modulators SPM-MMT, SPM-MST, SPM-MMT-Q and SPM-MST-Q

SPM 100 - TT

for SPM-TT

For SPM 100 and SPM 200 power supply NG 12/3000 is needed.

SPM 100 / SPM 100 - T / SPM 100 - TT / SPM 200

Type	SPM 100	SPM 100 - T	SPM 100 - TT	SPM 200	NG 12/3000
Article no.	5529000	5529600	5529001	5529050	9300610
Plug-in place	1			2	
Output level	105 dBμV			102 dBμV	
Operating voltage	12 V=			12 V=	100 - 240 V~/50/60 Hz
Output voltage	—			—	12 V= /3 A
Dimensions	40 x 285 x 145			87 x 294 x 147	Power supply

