



Model NV-208A-M Video Transceiver



Features:

- ▶ Full-motion CCTV video at distances up to 750ft (225m) when used with any passive NVT transceiver or hub
- ▶ Up to 3,000ft (1 km) with an NVT active receiver or hub
- ▶ Male BNC allows connection directly to the camera or DVR
- ▶ Features Screwless UTP terminal connection
- ▶ Supports "up-the-coax" type control signal up to 750ft (225m)
- ▶ No power required
- ▶ Exceptional interference rejection
- ▶ Built-in transient protection
- ▶ Limited lifetime warranty



The NVT Model NV-208A-M Video Transceiver is a passive (non-amplified) device that allows the transmission of real-time monochrome or color video over Unshielded Twisted-Pair (UTP) telephone wire. Baseband (composite) signals of any type are supported.

This product is an improvement over NVT's popular NV-213A video transceiver. The NV-208A-M features a Screwless UTP terminal block and Male BNC allowing connection directly to the camera or DVR. It is capable of delivering a fully equalized signal to the DVR when used with any Active NVT Receiver, yet is compatible with all of NVT's passive products for applications under 750ft (225m). The NV-208A-M Video Transceiver also incorporates new improved transient protection that eliminates the need for a ground screw.

The unparalleled interference rejection and low emissions of the NV-208A-M allow video signals to co-exist in the same cable bundle as telephone, datacom, or low-voltage power circuits. This allows the use of a shared or existing cable plant. As with all NVT products, the NV-208A-M carries a limited lifetime warranty and is UL and cUL listed and CE compliant.

Network Video Technologies Ltd

NVT House, 99 Waldegrave Road, Teddington, Middlesex TW11 8LA
Tel: +44 (0) 208 977 6614 • Fax: +44 (0) 208 973 1855 • uksales@nvt.com • www.nvt.com



Model NV-208A-M Video Transceiver

Technical Specifications

Video

Frequency response	DC to 5 MHz
Attenuation	0.5 dB typ
Common-mode / Differential-mode rejection 15 KHz to 5 MHz	60 dB typ
Impedance	
Coax, male BNC	75 ohms
UTP, Screwless terminal blocks	100 ohms

Power

No external power required

Environmental

Temperature	-20 to +75°C
Humidity (non-condensing)	0 to 95%
Transient Immunity	per ANSI / IEEE 587 C62.41

Wire Type

Network Wiring	One Unshielded Twisted Pair 24-16 AWG (0.5-1.31 mm)
Category Type	2 or better
Impedance	100 ± 20 ohms
DC Loop Resistance	52 ohms per 1,000 ft (18 ohms per 100 m)
Differential Capacitance	19 pF/ft max (62 pF/m max)

Mechanical

Body Length	1.7 inches (43mm)
Body Height	0.8 inches (21mm)
Body Width	0.6 inches (14.5mm)
Weight	1.1 oz (34 g)

Specifications subject to change without notice.

Network Video Technologies Ltd

NVT House, 99 Waldegrave Road, Teddington, Middlesex TW11 8LA
Tel: +44 (0) 208 977 6614 • Fax: +44 (0) 208 973 1855 • uksales@nvt.com • www.nvt.com