



WELFARE ELECTRONIC COMPONENT LTD.

UNIT C, G/F., MING CHU BLDG., 195-201 APLIU STREET, SHAMSHUIPO, KOWLOON, HONG KONG.
TEL: (852) 2786 0763 (HOT LINE), 2371 0368 (6 LINES) FAX: (852)-2786 0872

M-924MK2



- **Power Amplifier**
- 240W RMS
- 20 ~ 20,000Hz frequency response \pm 1dB
- Low distortion and noise level and excellent output regulation
- Built-in protection circuitry
- Full range of plug-in modules
- Input level switch (1,000mV/100mV)
- Rack mountable with optional mounting accessory MB-35B (3 unit size)

Specification

Output Power	• 120W RMS
Power bandwidth	20 ~ 20,000Hz, 0.5% THD/(T); 50 ~ 20,000Hz, 0.5% THD
Frequency Response	20-20 000 Hz \pm 1dB/(T); 20 ~ 15,000Hz, \pm 1dB
Input Sensitivity	1 input port / input port: 100mV or 1,000mV (switchable)/10k Ω / One direct input/Direct input; 100mV or 1,000mV (switchable)/10k Ω
Main (T) Output	8 Ω , 70V and 100V, balanced
Signal to Noise Ratio (Band Pass: 20 ~ 20,000Hz) with Tone Controls Centered	Input level switch in 0dBV (1,000mV) position; 108dB / Input level switch in -20dBV (100mV) position; 90dB
Controls	1 input gain control / 1 power on/off switch / 1 input level switch / 1 low cut switch
Protection	Self protection, with 2 AC fuses (1 inside) and 2 DC fuses.
Power Requirements	220/240V AC (switchable), 480VA
Dimensions (WxHxD)	420 x 151.3 x 334.2 mm
Weight (without input modules)	19.5 kg
Finish	Black