## **Σ-plus SERIES**



Engineered with cutting edge patented technology, stunning new designs, and updated features optimized for live stage demands, Carol's innovative Sigma Series mics define superior professional quality.



Σ-plus 1

(p.08)

Live Stage Performance Microphone
Wired Microphone

Polar Pattern: Supercardioid Frequency Response: 50Hz~18KHz Impedance: 3000 ± 30% Sensitivity: -73 ± 3dBV/µbar Dimension (mm): 651 x 178 Weight (without cable): 365 ± 10g



Σ-plus 2

(p.08)

Live Stage Performance Microphone
Wired Microphone

Polar Pattern: Supercardioid Frequency Response: 50Hz~18KHz Impedance: 3000 ± 30% Sensitivity: -74 ± 3dBV/µbar Dimension (mm): ø51 x 178 Weight (without cable): 360 ± 10g



Σ-plus 3

Live Stage Performance Microphone
Wired Microphone

Polar Pattern: Supercardioid Frequency Response: 50Hz-16KHz Impedance: 600Ω ± 30% Sensitivity: -73 ± 3dBV/μbar Dimension (mm): a54 x 178 Weight (without cable): 320 ± 10g



Σ-plus 5

Σ-plus 4

(p.12,

Live Stage Performance Microphone
Wired Microphone
Polar Pattern: Cardioid

Frequency Response: 50Hz $^{-1}8$ KHz Impedance:  $6000 \pm 30\%$  Sensitivity:  $^{-6}8 \pm 3$ dBV/Pa Power Supply:  $480 \times 10^{-6}$  Power Supply:  $480 \times 10^{-6}$  Power Dimension (mm):  $624.5 \times 141$  Weight (without cable):  $87 \pm 10q$ 



Σ-plus 5

(p.12

Live Stage Performance Microphone
Wired Microphone


Polar Pattern: Cardioid Frequency Response: 50Hz~18KHz Impedance: 6000 ± 30% Sensitivity: -68 ± 3dBV/Pa Power Supply: 5UM-3 x 1 pcs or

48V DC Phantom Power Dimension (mm):  $\emptyset 24.5 \times 197$  Weight (without cable):  $113 \pm 10g$ 



Live Stage Performance Microphone
Wired Microphone

Polar Pattern: Bidirectional Frequency Response: 30Hz-12KHz Impedance: 3000 ± 30% Sensitivity: -76 ± 3d8V/µbar at 1000Hz Dimension (mm): ø60 x 130





**Σ-plus 7** (p.13) *Live Stage Performance Microphone* 

Wired Microphone

Polar Pattern: Supercardioid Frequency Response: 50Hz~18KHz Impedance: 3000 ± 30% Sensitivity: ~73 ± 3dBV/µbar at 1,000Hz Dimension (mm): e51 x 100 Weight (without cable): 300 ± 10g



Σ-plus 6

Σ-plus 7