

# GS SERIES



GS-35

GS-56

GS-67

GS-77s

Our most affordable microphones, the GS series offers ultra-lightweight construction for enhanced comfort with uncompromised sound quality and durability. The ideal first microphone for all your entertainment needs.

## GS-35 (p.24)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 100Hz-10KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø53 x 182  
**Weight (without cable):** 184 ± 10g



## GS-36 (p.24)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 100Hz-10KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø53 x 165  
**Weight (without cable):** 195 ± 10g



## GS-55 (p.24)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 50Hz-15KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø52 x 178  
**Weight (without cable):** 232 ± 10g



## GS-56 (p.25)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 50Hz-15KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø52 x 178  
**Weight (without cable):** 229 ± 10g



## GS-57 (p.25)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 50Hz-15KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø48.2 x 173  
**Weight (without cable):** 214 ± 10g



## GS-67 (p.25)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz-16KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø48.2 x 176  
**Weight (without cable):** 212 ± 10g



## GS-77s (p.26, 67)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Cardioid  
**Frequency Response:** 50Hz-15KHz  
**Impedance:** 600Ω ± 30%  
**Sensitivity:** -72 ± 3dBV/ubar  
**Dimension (mm):** ø50 x 144  
**Weight (without cable):** 108 ± 10g



GS-36

GS-57

GS-55