

**502**

---

# Specifications

Version 1.0 January 2006

**XENYX**

[www.behringer.com](http://www.behringer.com)



## **XENYX 802**

---

# **XENYX**

### **Premium 5-Input 2-Bus Mixer with XENYX Mic Preamp and British EQ**

- ▲ Premium ultra low-noise, high headroom analog mixer
- ▲ State-of-the-art XENYX Mic Preamp comparable to stand-alone boutique preamps
- ▲ Neo-classic “British” 2-band EQ for warm and musical sound
- ▲ Main mix, stereo CD/tape plus separate headphone outputs
- ▲ CD/tape inputs assignable to headphone output or main mix outputs
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

502

## SPECIFICATIONS

### Mono inputs

#### Microphone input (XENYX Mic Preamp)

Type	XLR, electronically balanced, discrete input circuit
Mic E.I.N. (20 Hz - 20 kHz)	
@ 0 $\Omega$ source resistance	-134 dB / 135.7 dB A-weighted
@ 50 $\Omega$ source resistance	-131 dB / 133.3 dB A-weighted
@ 150 $\Omega$ source resistance	-129 dB / 130.5 dB A-weighted

Frequency response	<10 Hz - 150 kHz (-1 dB), <10 Hz - 200 kHz (-3 dB)
--------------------	---

Gain range	+10 to +60 dB
Max. input level	+12 dBu @ +10 dB gain
Impedance	approx. 2.6 k $\Omega$ balanced
Signal-to-noise ratio	110 dB / 112 dB A-weighted (0 dBu In @ +22 dB gain)

<b>Distortion (THD+N)</b>	0.005% / 0.004% A-weighted
---------------------------	----------------------------

### Line input

Type	1/4" TRS connector electronically balanced
Impedance	approx. 20 k $\Omega$ balanced 10 k $\Omega$ unbalanced
Gain range	-10 to +40 dB
Max. input level	+22 dBu @ 0 dB Gain

### Fade-out attenuation<sup>1</sup> (Crosstalk attenuation)

Main fader closed	90 dB
Channel muted	89.5 dB
Channel fader closed	89 dB

### Frequency response

Microphone input to main out	
<10 Hz - 90 kHz	+0 dB / -1 dB
<10 Hz - 160 kHz	+0 dB / -3 dB

### Stereo inputs

Type	1/4" TRS connector, electronically balanced
Impedance	approx. 20 k $\Omega$
Max. input level	+22 dBu

### EQ mono channel

Low	80 Hz / $\pm$ 15 dB
High	12 kHz / $\pm$ 15 dB

### Main outputs

Type	1/4" TRS connector, unbalanced
Impedance	approx. 120 $\Omega$ unbal.
Max. output level	+22 dBu

### Headphones output

Type	1/4" TRS connector, unbalanced
Max. output level	+19 dBu / 150 $\Omega$ (+25 dBm)

### Main mix system data<sup>2</sup>

Noise	
Main mix @ - $\infty$ ,	
Channel fader - $\infty$	-106 dB / -109 dB A-weighted
Main mix @ 0 dB,	
Channel fader - $\infty$	-95 dB / -98 dB A-weighted
Main Mix @ 0 dB,	
Channel fader @ 0 dB	-84 dB / -87 dB A-weighted

### Power supply

Power consumption	13W
-------------------	-----

### Mains voltage

USA/Canada	120 V~, 60 Hz, MXUL5 adapter
U.K./Australia	240 V~, 50 Hz, MXUK5 adapter
Europe	230 V~, 50 Hz, MXEU5 adapter
Japan	100 V~, 60 Hz, MXJP5 adapter

### Dimensions

Dimensions (H x W x D)	1 5/6" / 1 1/2" (47 mm / 37 mm) x 5 1/4" (134 mm) x 7" (177 mm)
Weight (net)	approx. 0.55 kg (1.21 lbs)

### Measuring conditions:

- 1 kHz rel. to 0 dBu; 20 Hz - 20 kHz; line input; main output; unity gain.
- 20 Hz - 20kHz; measured at main output. Channels 1 - 4 unity gain; EQ flat; all channels on main mix; channels 1/3 as far left as possible, channels 2/4 as far right as possible. Reference = +6 dBu.

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

---

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studioteknik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER Spezielle Studioteknik GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903

---