

UT60F

Modern Digital Multimeters



[Enlarge](#)



UL/cUL Pending
Registered Design No.: 0011438. 1M002

[Download Manual](#)

[Download Software](#)

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.5%+3)
AC Voltage	400mV/4V/40V/400V/1000V	±(1%+2)
DC Current	400µA/4000µA/40mA/400mA/10A	±(1%+2)
AC Current	400µA/4000µA/40mA/400mA/10A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Capacitance	4nF/40nF/400nF/4µF/40µF/400µF/4mF	±(4%+3)
Frequency	4kHz/40kHz/400kHz/4MHz/40MHz	±(0.05%+3)
Special Functions		
Fused 10A Range	✓	
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
RS232C	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	Around 312g
Product Size	177 x 73.5 x 35mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip RS232C Interface Cable, Software
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326 mm (0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 26kg

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

[Back to main menu](#)