

# UT106/UT107

**NEW**
**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy	
		UT106	UT107
DC Voltage	200mV/2V/20V/200V/1000V 200mV/2V/20V/1000V	$\pm(0.5\%+2)$	$\pm(0.5\%+2)$
AC Voltage	200V/750V	$\pm(0.8\%+5)$	$\pm(0.8\%+5)$
DC Current	200mA/10A	$\pm(0.8\%+5)$	$\pm(0.8\%+5)$
Resistance	200 $\Omega$ /2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /2M $\Omega$ /20M $\Omega$ 200 $\Omega$ /2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /20M $\Omega$	$\pm(0.8\%+5)$	$\pm(0.8\%+5)$
Temperature( $^{\circ}$ C)	-40 $^{\circ}$ C~1000 $^{\circ}$ C	$\pm(2\%+8)$	$\pm(2\%+8)$
Frequency	2kHz	$\pm(2\%+5)$	$\pm(2\%+5)$
Duty Cycle	1%~90%		$\pm(4\%+5)$
Special Functions			
Fused 10A Range		✓	✓
Battery Test	12V		$\pm(3\%+5)$
Dwell	4Cyl/6Cyl/8Cyl	$\pm(3\%+5)$	$\pm(3\%+5)$
Tach	4Cyl/6Cyl/8Cyl	$\pm(3\%+5)$	$\pm(3\%+5)$
Diode		✓	✓
Continuity Buzzer		✓	✓
Data Hold		✓	✓
Low Battery Display		✓	✓
Input Impedance for DC Voltage Measurement	Around 10M $\Omega$	✓	✓
Max. Display	1999	✓	✓

**GENERAL CHARACTERISTICS**

Power	9V Battery (6F22)
LCD Size	60 x 54 mm
Product Colour	<b>UT106/UT107</b> - Grey Holster - Red
Product Net Weight	352g
Product Size	179 x 88 x 39 mm
Standard Accessories	Test Lead, Battery, English Manual, Holster, Point Contact Temperature Probe
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	490 x 425 x 300 mm (0.062 CBM Per Standard Carton)
Standard Carton Gross Weight	23kg


**UT106**

**UT107**
**CE**