



EN:61010-1
EN:61326-1



■ UT521
WECL:59-03-0521



■ UT522



SPECIFICATIONS

| Specifications | Range | Best Accuracy | |
|------------------------------|--|---------------|----------|
| Model | | UT521 | UT522 |
| Earth Resistance (Ω) | 0~20Ω | ±(2%+10) | |
| | 0~200Ω | ±(2%+3) | |
| | 0~2000Ω | ±(2%+3) | |
| | 0~40Ω | | ±(2%+20) |
| | 0~400Ω | | ±(2%+3) |
| | 0~4000Ω | | ±(2%+3) |
| AC Earth Voltage (V) | 0~200V | ±(1%+4) | |
| | 0~400V | | ±(1%+6) |
| | Frequency: 50Hz/60Hz | ✓ | ✓ |
| Features | | | |
| Display Count | | 2000 | 4000 |
| Manual Range | | ✓ | ✓ |
| Auto Power Off | Around 10 Minutes | ✓ | ✓ |
| Low Battery Indication | | ✓ | ✓ |
| Data Hold | | ✓ | ✓ |
| Data Logging | | 20 | 20 |
| LCD Backlight | | ✓ | ✓ |
| Full Icon Display | | ✓ | ✓ |
| Double Insulation Protection | | ✓ | ✓ |
| Contact Badness Display | Port C or Port E No contact Display"----Ω" | ✓ | ✓ |
| Over-Range Display | Display "OL" | ✓ | ✓ |
| Simple 2-Wires Testing | | ✓ | ✓ |
| Precision 3-Wires Testing | | ✓ | ✓ |

GENERAL CHARACTERISTICS

| | |
|------------------------------|--|
| Power | 1.5V Alkaline Batteries (LR6) ×6 |
| LCD Size | 70.6mm × 34mm |
| Product Color | Red and Grey |
| Product Net Weight | 560g |
| Product Size | 160mm × 100mm × 70.5mm |
| Standard Accessories | Batteries, Carrying Bag, Test Lead, Simple Test Lead, Test Probe |
| Standard Individual Packing | Gift Box, English Manual |
| Standard Quantity Per Carton | 8 PCs |
| Standard Carton Measurement | 615 × 530 × 190mm (0.062 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 15 Kg |

