

330 Series Clamp Meters



Take a new look at current measurements

The Fluke 330 Series Clamp Meters offer all the features you need to fit the way you work. The small body and jaws fit perfectly in your hand and into tight places. Meter controls are positioned so that current measurements can be done with one hand. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display.

Measuring starting current for motors, lighting, etc. is easy with the in-rush current function (on most models). All models are backed up with a 3 year warranty.

Features

Functions	333	334	335	336	337
True-RMS			●	●	●
Display backlight		●	●	●	●
Auto shut-off	●	●	●	●	●
Display Hold	●	●	●	●	●
Motor start-up current		●	●	●	●
Low battery indication	●	●	●	●	●
Large jaw				●	●
Min/Max					●
Current AC/DC				●	●

Specifications

Functions	Range	333	334	335	336	337
Current AC	0-400.0A	2% ± 5 counts				
	0-600.0A		2% ± 5 counts	2% ± 5 counts	2% ± 5 counts	
	0-999.9A					2% ± 5 counts
Crest Factor	0-600.0A			2.4 @ 500A	3 @ 500A	
				2.0 @ 600A	2.5 @ 600A	
	0-999.9A					3 @ 500A 2.5 @ 600A 1.42 @ 1000A
Current DC	0-600.0A				2% ± 5 counts	
	0-999.9A					2% ± 5 counts
In-rush Current	Integration time		100mS	100mS	100mS	100mS
Voltage AC	0-600.0V	1% ± 5 counts				
Voltage DC	0-600.0V	1% ± 5 counts				
Resistance	0-600.0Ω	1.5% ± 5 counts				
	0-6000 Ω	1.5% ± 5 counts				
Continuity		≤ 30Ω				
Frequency						0.5% ± 5 counts



Included Accessories

C33 Soft case, TL75 test leads, 2 AA alkaline batteries, instruction card and safety information sheet.

Ordering Information

Fluke 333	Clamp Meter
Fluke 334	Clamp Meter
Fluke 335	True-RMS Clamp Meter
Fluke 336	True-RMS Clamp Meter
Fluke 337	True-RMS Clamp Meter

Battery Life: Alkaline, 150 hours

Size (HxWxD):

238 mm x 79 mm x 41mm (333, 334 and 335)

251 mm x 79 mm x 41 mm (336 and 337)

Jaw Opening: 30 mm (333, 334, 335)

42 mm (336, 337)

Weight: 0.312 kg

Three Year Warranty

Recommended Accessories



H3



TL223



L215