



CENTER 322 Sound Level Meter

- **RS-232 Interface**
- **32,000 Records Datalogger**
- **Bar Graph Indication**
- **MAX/MIN Function**
- **Auto Ranging(30~130dB)**
- **Resolution 0.1dB**
- **Clock Display**
- **Level Range Display**

Microphone:

Electorate condenser microphone

Accuracy:

±1.5 dB (ref 94dB @1KHz)

Level Range:

Lo = 30 ~ 80 dB
Med = 50 ~ 100 dB
Hi = 80 ~ 130 dB
Auto=30~130 dB

Frequency Weighting:

A , C

Time Weighting:

Fast , Slow

Auxiliary Outputs:

AC output

Output voltage: 1Vrms (at full scale)

Output impedance: Approx:600Ω

AC output

Output voltage: 10mV / dB

Output impedance: Approx:50Ω

Dynamic Range:

50 dB

Frequency Range:

31.5Hz to 8KHz

Battery Type:

9V Battery

Battery Life:

50 hours (with alkaline battery)

Operation Temp.:

0° C~ 40° C(<80% R.H.) 9V Battery, Carrying Case, Calibration Screwdriver, Windscreen

Accessories:

Battery, Operation Manual, Carrying Case, Calibration Screwdriver, Windscreen, 3.5Φ plug Software, RS-232