



Multi-Charger for Ni-MH and Ni-Cd Batteries

NC-MQH01



Features

- Charges AA or AAA batteries separately or simultaneously
- Auto voltage (AC 100-240V)
- Overcharge protection
- Protective mechanism that automatically stops charging if non-rechargeable batteries are accidentally inserted
- Quick charge (70 min. for 2 x AA batteries)
- Compact and lightweight
- Built-in battery capacity checker

Copyright (C) 2004 SANYO Sales & Marketing Corporation. All rights reserved.

Battery Chargers

Model no.	Voltage(V)	No. of batteries	Charging time							LED Lamp	AC Power	Dimensions (L X W X H mm)	Weight (approx.)
			Ni-MH				Ni-Cd						
			AA(2300mAh)	AA(2100mAh)	AA(1700mAh)	AAA(800mAh)	AA(1100mAh)	AA(750mAh)	AAA(270mAh)				
NC-MQR02	100-240(Auto Voltage)	1 or 2	115 min..	105 min..	85 min.	155 min.	50 min.	35 min.	50 min.			105 X 65 X 27.5	95g
		3 or 4	255 min.	230 min.	195 min.	-	110 min.	80 min.	-				
NC-MQN01N	100-240(Auto Voltage)	1 or 2	-	-	7.5 hrs.	6.0 hrs.	5.5 hrs.	3.5 hrs.	2.0 hrs.			105 X 65 X 26	90g
		3 or 4	-	-	7.5 hrs.	-	5.5 hrs.	3.5 hrs.	-				
NC-MQH01	100-240(Auto Voltage)	1 or 2	70 min.	64 min.	55 min.	70 min.	-	-	45 min.			120 X 80 X 32	150g
		3 or 4	155 min.	140 min.	110 min.	-	100 min.	70 min.	-				
NC-MQR03	100-240(Auto Voltage)	1 or 2	115 min..	105 min..	85 min.	155 min.	50 min.	35 min.	50 min.			105 X 65 X 27.5	100g
		3 or 4	255 min.	230 min.	195 min.	-	110 min.	80 min.	-				
NC-MQS01	100-240(Auto Voltage)	1 to 4	30 min.	30 min.	30 min.	60min.	-	-	-			120 X 40.5 X 91	150g (without AC adapter)
NC-MQN02	100(Japan), 120V(North America), 220V(China), 230V(Europe/Aisa), 240V(Australia)	2	-	-	10 hrs	8 hrs.	6.5 hrs.	4.5 hrs.	3 hrs.			113 X 66 X 37	230g
		4	-	-	10 hrs	8 hrs.	6.5 hrs.	4.5 hrs.	3 hrs.				