

Fluxclene Cleaning Solvent

Product Code: FLU

PRODUCT DESCRIPTION

Fluxclene is a fast-drying solvent cleaner specially formulated for the quick and efficient removal of flux residues after soldering. It can replace ozone depleting solvents such as CFC 113 and exhibits rapid cleaning and fast evaporation rates. The cleaning power of **FLU** exceeds that of traditional CFC based solvents, easily giving MIL-STD cleanliness.

PRODUCT USE

Fluxclene contains **flammable solvents** so do not spray onto live electrical equipment or other sources of ignition. Immerse surface to be cleaned or spray onto surface to excess and allow to evaporate. A brush or foam tipped bud may be used to remove any stubborn deposits. For use for large scale production, FLU may be used in ultrasonic cleaning equipment which must be adapted for use with flammable liquids.

FEATURES

- * 100% ozone friendly solvent - i.e. zero ODP.
- * Excellent removal of greases, oils and flux residues and acrylic conformal coatings from printed circuit boards (PCBs).
- * Leaves a perfectly clean, dry surface - conventional solvents often leave greasy deposits which attract dust and dirt.
- * Harmless to most plastics, rubbers, elastomers, and surface coatings.
- * CO₂ propelled aerosol version available containing 20% more active cleaner, fitted with a 360° valve for use in any orientation. Also available in aerosol form with integral brush.

TECHNICAL
DATA
SHEET



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Fluxclene Cleaning Solvent – Page 2

TYPICAL PROPERTIES

Specific Gravity @ 20°C:	0.78
Inhalation Toxicity:	300 ppm
Flash Point:	0°C (estimate)
Residue on Evaporation:	<1ppm
Evaporation Rate:	16 (with ether as 1)

PACKAGING

200ml Aerosol
400ml Aerosol with brush
400ml Aerosol
1 Litre Bulk
5 Litre Bulk

ORDER CODE

FLU200D
FLU400DB
FLU400D
FLU01L
FLU05L

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

