

Bloc'Lube

Product Code: BLR/BLV

PRODUCT DESCRIPTION

Electrolube Bloc'Lube is a one part, air-drying, tamper evident seal for screws, nuts, tuneable items and other "factory fixed" components where evidence of unauthorised access is required. It is also ideal for application onto rotary controls to ensure that settings do not move under vibration loads etc. It offers good anti-fungal properties and resists mould growth.

Bloc'Lube is available as a red or green lacquer.

TYPICAL PROPERTIES

Colour:	Red or Green
Flash Point:	3.3°C
Shelf Life	48 Months

DIRECTIONS FOR USE

Bloc'Lube should be applied directly onto the component with the brush contained in the lid of the bottle. It should be applied in an even film in sufficient quantity to be easily visible.

The coating will be tack free after 10 minutes but remains flexible for up to 24 hours. This is to allow fine tuning. After this time the seal will become brittle and any interference or tampering will break the seal and become self-evident.

REMOVAL

Bloc'Lube is usually removed physically with a screwdriver or similar. Any chips remaining may be removed using **Electrolube Ultrasolve** or **Printasolve** (take care with these solvents on sensitive plastics)

PACKAGING

Bloc'Lube - Red
Bloc'Lube - Green

ORDER CODE

BLR15ML
BLV15ML

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

