

APC Smart-UPS 750VA USB & Serial 230V

APC Smart-UPS, 750VA/500W,
Input 230V/Output 230V,
Interface Port DB-9 RS-232, USB,
SmartSlot

Includes: CD with software, Smart UPS
signalling RS-232 cable, USB cable,
User Manual

Part Number : **SUA750I**



.....

Technical Specifications

[Output](#)

Output power capacity	750 VA
Output power capacity	500 Watts
Max Configurable Power	750 VA
Max Configurable Power	500 Watts
Nominal output voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	less than 5% at full load
Output Frequency (sync to mains)	47-53Hz for 50Hz nominal, 57-63Hz for 60Hz nominal
Crest Factor	up to 5 : 1
Waveform type	Sinewave
Output Connections	(6) IEC 320 C13  (2) IEC Jumpers

[Input](#)

Nominal input voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connection Type	IEC-320-C14 inlet
Input voltage range for main operations	160 - 285 V
Input voltage adjustable range for mains operation	151 - 302 V

[Batteries & Runtime](#)

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

User Manual & Installation

Guides:

 [Smart-UPS 500/750 VA, 100/120/230 V \(Manual\)](#)

Features:

- Battery replacement without tools
- Disconnected battery notification
- Front-access servicing
- USB Connectivity

General Features:

- Adjustable voltage sensitivity
- Adjustable voltage-transfer points
- Audible Alarms
- Automatic restart of loads after UPS shutdown
- Automatic self-test
- Boost and Trim Automatic Voltage Regulation (AVR)
- Cold-start capable
- Generator Compatible
- Hot-swappable batteries
- Intelligent Battery Management
- LED status indicators
- Network manageable
- Power conditioning
- Predictive failure notification
- Resettable circuit breakers
- Safety-agency approved
- Serial Connectivity
- SmartSlot
- Temperature-compensated battery charging

[more details...](#)

Topology: Line Interactive