

Wireless Internet Camera CAS-200W



Specification

Bundled Software

- IPView Application

Video specification

Resolution:	640 x 480 pixels
Sensor:	Color CMOS sensor
Gain Control:	Automatic
Exposure:	Automatic
White Balance:	Automatic
Signal/Noise Ratio:	57dB
Focal Length:	6.0 mm
Aperture:	F=1.8
Focus Extent:	20 cm - 8
Lens mounting	CS-mount type

Image (Video Setting)

Image Compression:	JPEG
Frame rate:	20fps@SIF , 6fps@VGA
Compression Rate selection:	Auto
Frame rate setting:	1, 5, 7, 15, 20, auto
Video resolution:	320x240, 640x480
Brightness control:	Yes
Contrast control:	Yes
Saturation:	Yes

System Hardware

LAN Connector:	One RJ-45 port to connect to 10/100Mbps Ethernet, auto-sensed
Wireless LAN:	Built-in 802.11b wireless LAN module (Wi-Fi compliant)
Generic I/O Port:	Input Port x 2 & Output Port x 2
LED Indicator:	Power LED LAN/WLAN Activity LED
Power Supply:	DC 5V, switching type
Power Consumption:	6.5 Watt (1300mA x 5V)
Slide Switch:	LAN/LAN&WLAN/WLAN
Antenna Connector:	2 connectors

Communication Support

Communication:	10/100TX Ethernet only 10/100TX Ethernet and 802.11b wireless LAN 802.11b wireless LAN only
----------------	---------------------------------------------------------------------------------------------------

Encryption: 64 bit, 128 bit or OFF

Communication protocol: HTTP, FTP, TCP/IP, UDP, ARP, ICMP, BOOTP, RARP, DHCP, PPPoE

Browser Support

- Internet Explorer 5.0 or above (ActiveX & JAVA Mode – View Image for windows OS and JAVA Mode – View Image for other OS)
- Netscape 6.0 or above (JAVA Mode – View Image)

IPView Application Software

Support OS: Win 98 SE, Win 2000, Win Me, Win XP

Upgrade

Firmware remotely upgrade

EMI

FCC, CE, VCCI

Deployment Diagram



Ordering Information

CAS-200WA2 / ANA Wireless Internet Camera, USA type wireless card. 100-120V input with USA & Japan plug

CAS-200WA2 / BEU Wireless Internet Camera, European type wireless card. 200-240V input with UK plug

CAS-200WA2 / EEU Wireless Internet Camera, European type wireless card. 200-240V input with Europe plug

CAS-200WA2 / EFR Wireless Internet Camera, French type wireless. 200-240V input with Europe plug

CAS-200WA2 / NEU Wireless Internet Camera, European type wireless card. 200-240V input with Australia plug

CAS-200WA2 / AJP Wireless Internet Camera, Japan type wireless. 100-120V input with USA & Japan plug

All specifications are subject to change without notice